



imagePROGRAF TX-3200

ENGINEERED FOR PRODUCTIVITY IN HIGH VOLUME PRINT ENVIRONMENTS

Accelerate printing with a sustainable 5-colour 36" printer which exemplifies impressive productivity, enhanced ease of use, professional image quality, and robust security. Designed for sizable corporates, government, print service providers in AEC&M sector.

BENEFITS

- **Impressive productivity**
Enhance productivity with print speed of 3.3 ppm(A1) and minimise downtime with 30% faster media exchange, dual roll configuration and hot swap ink tanks allow replacement during operation. Minimise misprints with colour calibration, print head monitoring and auto adjustments.
- **Enhanced ease of use**
Enjoy seamless workflow processes via auto media loading, simplified media settings, an intuitive interface, and Direct Print Plus - a free job submission tool that minimises misprints by previewing documents.
- **Professional image quality**
Produce high-quality output with water-resistant pigment ink, create distinct layers in CAD drawings via new magenta ink and ensure prints are as precise as can be with razor-sharp lines and vivid colours.
- **Robust security**
From enhanced encrypted communications and secure PIN code printing to the advanced authentication process and secure hard drive erasure, the imagePROGRAF TX-3200 offers the highest level of protection for your documents, devices and network.
- **Support sustainability**
The imagePROGRAF TX-3200 is a sustainable printer with an EPEAT Gold* rating for energy efficiency and packaging that's free from expanded polystyrene (EPS).

*EPEAT Gold registered in the U.S.

Canon

TECHNICAL SPECIFICATIONS

imagePROGRAF TX-3200

PRINTER TECHNOLOGY

Printer Type	5 Colours 36"
Print Technology	Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head)
Print Resolution	2,400 x 1,200 dpi
Number of Nozzles	Total: 15360 nozzles MBK: 5120 nozzles BK, C, M, Y: 2560 nozzles each
Line Accuracy	±0.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments.
Nozzle Pitch	1,200 dpi x 2 lines
Ink Droplet Size	minimum 5pl per colour
Ink Capacity	Bundled Starter Ink: 970ml (330ml for MBK, 160ml for others) Sales Ink: 160ml / 330ml / 700ml
Ink Type	Pigment inks : 5 colours MBK/BK/C/M/Y
OS Compatibility	32 Bit: Windows7, Windows 8.1, Windows 10 64 Bit: Windows 7, Windows 8.1, Windows 10, Windows 11, Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 Apple Macintosh: macOS 11.7.10~macOS 14.x
Others supported job submission protocol	Apple AirPrint
Printer Languages	HP-GL/2, HP RTL, PDF (Ver. 1.7), JPEG (Ver. JFIF1.02), CALS G4 (submission via FTP only)
Standard Interfaces	USB A Port:USB Memory (Direct Print) USB B Port: Hi-Speed USB Ethernet: IEEE802.3ab(1000base-T), IEEE802.3u(100BASE-TX)/IEEE802.3(10BASE-T), IEEE 802.1X (EAP-TLS/EAP-TTLS/PEAP) Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b
	*Please refer to user manual how to activate/deactivate the wireless LAN

MEMORY

Standard Memory	128GB (Physical memory 2GB) Expansion slot : No
Hard Drive	500GB(Encrypted)

PRINTING SPEED

CAD Drawing	Plain Paper (A1) 0:17 (Fast Economy Mode): 3.3ppm Plain Paper (A0) 0:32 (Fast Economy Mode) 0:35 (Fast) 1:06 (Standard)
--------------------	--

MEDIA HANDLING

Media Feed and Output	Roll Paper : One Roll, Front-loading, Front Output Added Roll Paper: One Roll, Front-loading, Front Output Cut Sheet : Front-loading, Front Output (Manual feed using media locking lever)
Media Width	Roll paper: 152.4mm - 917mm Cut sheet: 152.4mm - 917mm
Media Thickness	Roll/Cut : 0.07mm - 0.8mm
Minimum Printable Length	Roll paper: 101.6mm (excluding cloth, tracing paper and translucent matte film media. These media are 200mm) Cut sheet: 203.2mm
Maximum Printable Length	Roll paper : 18m (varies according to the OS and application) Cut sheet : 1.6m
Maximum Media Roll Diameter	170mm
Media Core Size	Internal diameter of roll core: 2 7/3"
Margins Recommended Area	Roll paper: Top: 20mm, Bottom: 3mm, Side: 3mm Cut sheet: Top: 20mm, Bottom: 20mm, Side: 3mm Cut sheet (AppleAirPrint): Top: 20mm, Bottom: 31mm, Side: 3mm
Margins Printable Area	Roll paper: Top: 3mm, Bottom: 3mm, Side: 3mm Roll paper (borderless): Top: 0mm, Bottom: 0mm, Side: 0mm Cut sheet: Top: 3mm, Bottom: 20mm, Side: 3mm Cut sheet (AppleAirPrint): Top: 3mm, Bottom: 12.7mm, Side: 3mm
Media Feed Capacity	Roll Paper: Two rolls. Automatic switching is possible. Roll Paper, Cut Sheet: Manual switching is possible Cut Sheet: 1 sheet
Media Take-Up Roll Unit	Dual direction roll take up unit allowing print surface to be wound inside or outside of the roll

Borderless Printing Width (Roll Only)

Maximum Number of Delivered Prints

POWER AND OPERATING REQUIREMENTS

Power Supply

Power Consumption

Operating Environment

Acoustic Noise (Power/Pressure)

Regulations

Environment Certificates

DIMENSIONS AND WEIGHT

Physical Dimensions and Weight

Packaged Dimensions and Weight

WHAT'S INCLUDED

What's in the Box?

Software Included

OPTIONS

Optional Items

CONSUMABLES

User Replaceable Items

[Recommended] 515mm(JIS B2), 728mm(JIS B1), 594mm(ISO A1), 841mm(ISO A0), 10", 14", 17", 24", 36"
[Printable] 257mm(JIS B4), 297mm(ISO A3), 329mm(ISO A3+), 364mm (JISB3), 420mm(ISO A2), 707mm (ISO B1), 6", 8", 12", 15", 16", 18", 20", 22", 30", 34", 300mm, 500mm, 600mm, 800mm and custom roll width (152.4 - 917mm)
("Printable" size is printed as micro margin technology, that means it is not used with hole of platen)

[Multi-position basket]
Standard position: 1 sheet
Flat position: ISO landscape, glossy paper 10 sheets, coated paper 20 sheets, uncoated paper 20 sheets (excludes strong curled condition)

[Stacker]
Basket position : 1 sheet (excludes curled condition)
Folding position : A0/A1 portrait, CAD drawing, uncoated paper 90gsm 20 sheets, uncoated paper 100 sheets (excludes curled condition)
Flatbed position : A1/A2 landscape, CAD drawing, uncoated paper 90gsm 20 sheets, uncoated paper 100 sheets (excludes curled condition)

AC 100-240V (50-60Hz)

Operation: 86W or less
Sleep mode: 2.2W or less
Default setting for the time to enter the Sleep mode: Approx. 5 minutes
Power off: 0.1W or less

Temperature: 15-30°C, Humidity: 10-80% RH (no dew condensation)

Operation: Approx. 51dB(A) (Standard Plain Paper 2, Standard mode, Line Drawing/Text mode) (Measured based on ISO7779 standard)
Standby: 35 dB(A) or less
Operation: 6.9 Bels or less (Standard Plain Paper 2, Standard mode, Line Drawing/Text mode) (Measured based on ISO7779 standard)

CE mark, UKCA mark

CB certification, EPEAT GOLD¹

W x D x H
Main unit with stand
1390 x 984 x 1168 mm (Basket Opened)
1390 x 766 x 1168 mm (Basket Closed)
103kg (including Roll Holder Set, excluding ink and print head)

Printer (Main unit with pallet): 1626 x 903 x 1033 mm, 157kg
Roll unit: 1524 x 562 x 461 mm, 31kg

Printer, Printer Stand, 1 Print head, Power Cable, 1 Set of starter ink tanks, 1 Roll holder (spool), 3" Paper Core Attachment, Installation Guide, Safety/Standard Environment leaflet, LFP Eur Address Sheet, Important Information Sheet, Printer Stand Setup Guide, Notice for PosterArtist WEB

Software available as Download from Web

27/3" Roll Holder: RH2-34
Roll Unit: RU-32
Stacker: SS-31
IC card reader holder: RA-01

Ink Tank: M: PFI-111(160ml)/PFI-311(330ml)/PFI-711(700ml)
MBK/BK/C/Y: PFI-110(160ml)/PFI-310(330ml)/PFI-710(700ml)
Print Head: PF-06
Cutter Blade: CT-07
Maintenance Cartridge: MC-30

FOOTNOTE

1. EPEAT Gold registered in the U.S.

DISCLAIMER

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.



Canon Inc.
Canon.com

Canon Europe
canon-europe.com

English Edition
© Canon Europa N.V. 2024