

# iPF770



## Large Format Print Solutions ideal for CAD & GIS

The imagePROGRAF iPF770 is a 36"/A0 printers, delivering class leading productivity, exceptional quality, accuracy and an advanced set of features to ensure an excellent return on investment.



### Key features:

- High-volume continuous printing, with 130 ml hot-swap ink tanks that can be replaced while the unit is printing
- A0 output in Fast Economy mode in 48 seconds
- Space saving - Unique compact design to fit anywhere
- Highly accurate with 0.02 mm minimum line width and +/-0.1 % line accuracy
- 5-colour dye-and-pigment ink system with new magenta ink for reproduction of brighter red colour
- Printing PDF / TIFF / JPEG / HP-GL2 easily, from general graphics to CAD and GIS drawings, with bundled Direct Print & Share Utility
- Cloud ready for immediate sharing, with easy access even from mobile devices
- Use the bundled PosterArtist Lite software and Print Plug-in for Microsoft Office to create powerful large format posters with ease
- Manage costs and track ROI with full accounting tools

iPF770

**36**  
INCH

2,400 X  
1,200 DPI

130 ML  
INK TANKS

ECONOMY  
PRINTING MODE

5 COLOUR WITH  
NEW MAGENTA

A0 48 SECONDS

15,360  
NOZZLES

BORDERLESS  
PRINTING

**Canon**

## TECHNOLOGY

<b>Printer Type</b>	5 Colour – 36" / 914.4 mm
<b>Print Technology</b>	Canon inkjet on Demand 6 colours integrated type (6 chips per print head x 1 print head)
<b>Number of Nozzles</b>	Total: 15,360 MBK: 5,120 nozzles C, M, Y, BK: 2,560 nozzles each
<b>Print Resolution</b>	2,400 x 1,200 dpi
<b>Nozzle Pitch</b>	1,200 dpi x 2
<b>Guaranteed Minimum Line Width</b>	0.02 mm
<b>Line Accuracy</b>	±0.1 % or less
<b>Ink Droplet Size</b>	4 Picoliter per colour
<b>Ink Capacity</b>	Bundled Starter Ink: 90 ml Sales Ink: 130 ml
<b>Ink Type</b>	Dye / Pigment Reactive Ink Dye: Cyan, Magenta, Yellow, Black Pigment: Matte Black
<b>OS Compatibility</b>	32 bit – Windows XP, Windows Vista, Windows 7, Windows 8, Windows 8.1, Windows Server 2003 / 2003R2, Windows Server 2008 64 bit – Windows Vista, Windows 7, Windows 8, Windows 8.1, Windows Server 2003 / 2003R2, Windows Server 2008 / 2008R2, Windows Server 2012 / 2012R2 Mac: OSX – 10.6.8 – 10.10.x
<b>Printer Languages</b>	GARO (Graphic Arts Language with Raster Operations), HP-GL/2, HP RTL
<b>Standard Interfaces</b>	USB 2.0 High-Speed Ethernet 10 / 100 / 1000 Base-T/TX

## PRINTING SPEED

<b>A0 Size, Plain Paper</b>	0:48 min (Fast Economy Mode) 0:48 min (Fast Mode) 1:15 min (Standard Mode)
<b>A0 Size, Coated Paper</b>	1:15 min (Fast Mode) 2:24 min (Standard Mode) 3:50 min (High Quality Mode)

## MEMORY

<b>Buffer RAM</b>	256 MB
-------------------	--------

## PAPER HANDLING

<b>Media Width</b>	Roll Paper: 10" / 254 mm – 36" / 914.4 mm Cut Sheet: 8" / 203.2 mm – 36" / 914.4 mm
<b>Media Thickness</b>	Roll Unit: 0.07 – 0.8 mm Top Loading Manual Feed: 0.07 – 0.8 mm
<b>Minimum Printable Length</b>	Roll: 203.2 mm Cut Sheet: 279.4 mm
<b>Maximum Printable Length</b>	18 m (Varies according to the OS and application)
<b>Maximum Media Roll Diameter</b>	150.0 mm

## Paper Feed Method

## Borderless Printing Width (Roll Only)

## DIMENSIONS AND WEIGHT

### Physical Dimensions (W x D x H)

### Weight

### Software Included

Roll Feed: One Roll, Top Loading, Front Output  
Top Loading Manual Feed: One Sheet, Front Output  
10" (254 mm), B4 (257 mm), A3 (297 mm), Banner (300 mm), 14" (356 mm), A2 (420 mm), A2+/17" (432 mm), B2 (515 mm), A1 (594 mm), 24" (610 mm), B1 (728 mm), A0 (841 mm), 36" (914 mm)

1,304 (W) x 887 (D) x 1,062 (H) mm (With basket open)  
1,304 (W) x 1,100 (D) x 1,062 (H) mm (When basket is at the extended position for flatbed stacking)

64.6 kg (roll holder included, no inks, no print heads)

Canon Printer Driver, Status Monitor / Print Monitor, Printer Driver ExtraKit – Free Layout and iR enlargement Copy, Printer Driver Optimization Module for AutoCAD, Media Configuration Tool, PosterArtist Lite (PC only), Print Plug-in for Microsoft® Office (PC only), Direct Print & Share, Custom Installer Creation Tool

## POWER AND OPERATING REQUIREMENTS

### Power Supply

AC 100 – 240 V (50 – 60 Hz)

### Power Consumption

Operation: 140 W or less  
Power Off Standby: 0.5 W or less

### Operating Environment

15 – 30°C, 10 – 80 % (Condensation free)

### Noise Level (Approx.)

Operation: approx. 48 dB  
Standby: 35 dB or less  
Acoustic Power: 6.5 Bels  
Based on ISO 7779

## Regulations

Europe: CE mark,  
Germany: TUV mark,  
Russia: EAC  
Other Countries: CB Certification

## Environment

### Certificates

ENERGY STAR, RoHS (EU), WEEE (EU), ErP Directive (Lot6, 26), China RoHS, Chemical Substances Regulation, Battery certification (EU, Japan, USA, China, Taiwan), Packing material Regulation (EU, USA, Korea)

## WHAT'S INCLUDED

### What's In The Box?

1 print head, 1 set of starter ink tanks (C, M, Y, BK, 2 x MBK - 90 ml), 3 inch core adapters, set up guide, User software CD-ROM (Mac & Win), Carrying caution leaflet, Safety / Standard Environment leaflet, PosterArtist Lite leaflet, PosterArtist Lite software CD-ROM, Announcement of LFP Survey Program, EAC leaflet, Quick guide

## OPTIONS

### Roll Holder Set

RH2-33

## CONSUMABLES

### Ink Tanks

PFI-107: 130 ml – C, M, Y, BK, 2 x MBK

### Print Head

PF-04

### Maintenance Cartridge

MC-10



Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.

Canon Inc.  
canon.com  
Canon Europe  
canon-europe.com  
English edition  
© Canon Europa N.V., 2014

Canon (UK) Ltd  
Woodhatch  
Reigate  
Surrey RH2 8BF  
Telephone no 01737 220000  
Facsimile 01737 220022  
canon.co.uk

Canon Ireland  
3006 Lake Drive  
Citywest, Saggart  
Co. Dublin, Ireland  
Telephone No: 01 2052400  
Facsimile No: 01 2052525  
canon.ie

